




1177mm

1457mm


	1177mm			1457mm		
	CRI 80	13W	16W	26W	21W	33W
<b>3 Warm White LED (3000K)</b>						
Lumen Output	2507 lm	3132 lm	4887 lm	3957 lm	5944 lm	
LOR	0.79	0.79	0.79	0.79	0.79	
CRI	80	80	80	80	80	
Total Power	14.5W	18.3W	29.2W	23.6W	36.4W	
Power Factor	0.95	0.95	0.95	0.95	0.95	
Running Current	0.07A	0.10A	0.13A	0.11A	0.17A	
Inrush Current (Std)	5A (50us)	5A (50us)	7A (13us)	5A (50us)	7A (13us)	
Inrush Current (Dim)	10A (2.8us)	10A (2.8us)	12A (2.8us)	10A (2.8us)	12A (2.8us)	
Efficacy	136 lm/W	135 lm/W	132 lm/W	132 lm/W	129 lm/W	
Emergency Output (BLF)	N/A	N/A	N/A	N/A	N/A	
<b>4 Neutral White LED (4000K)</b>						
Lumen Output	2659 lm	3321 lm	5183 lm	4196 lm	6304 lm	
LOR	0.79	0.79	0.79	0.79	0.79	
CRI	80	80	80	80	80	
Total Power	14.5W	18.3W	29.2W	23.6W	36.4W	
Power Factor	0.95	0.95	0.95	0.95	0.95	
Running Current	0.07A	0.10A	0.13A	0.11A	0.17A	
Inrush Current (Std)	5A (50us)	5A (50us)	7A (13us)	5A (50us)	7A (13us)	
Inrush Current (Dim)	10A (2.8us)	10A (2.8us)	12A (2.8us)	10A (2.8us)	12A (2.8us)	
Efficacy	144 lm/W	143 lm/W	140 lm/W	140 lm/W	136 lm/W	
Emergency Output (BLF)	N/A	N/A	N/A	N/A	N/A	

Venue® Track



LED

Power	LED	Length	Beam Angle	Beam Diameter	Beam Spread	Beam Depth
13W	LED	1177mm	1682	13	777	777
16W	LED	1177mm	1682	16	777	777
26W	LED	1177mm	1682	26	777	777
21W	LED	1457mm	1684	21	778	778
33W	LED	1457mm	1684	33	778	778



230V 50-60Hz IP20 1.49 kg 1177mm 1.8 kg 1457mm

- Available in a choice of lumen output up to 6304 lumens
- Efficacies up to 144 lm/W
- Life expectancy 72,000 hours (L80 B10)
- Complementary Pendant & Surface versions available
- Quick and easy, tool free installation
- Wireless Lighting Control available, see Connected video for full overview
- Tamper proof end caps option available
- CRI90 options available TT/TD1683 & TT/TD1685

- TT Dali Track - Not suitable for use with Gear Types J & S
- TD Three Circuit Track - Not suitable for use with Gear Types A & L
- A Integral Driver/Remote
- J Switch Dim
- S DALI Dim
- L DALI Bluetooth
- 3 Warm (3000K) 4 Neutral (4000K)
- 1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)
- 640 Tamper Proof End Caps

Tel: (0191) 280 9911 Email: technical@hacel.co.uk Web: www.hacel.co.uk VI - 11/2024


\* All values provided in this document are subject to International standards and electronic components from leading suppliers which are subject to +/- 10% tolerance and apply at an ambient temperature of 25°C. Hacel Lighting look to constantly improve it's product and reserve the right to change specifications without prior notification.





## Venue® Track

### Photometrics



**777-778** DLOR: 0.79